

Slope

Specification Sheet

Project Name: _____

Job Location: _____

Fixture Type: _____

Fixture Quantity: _____

Source	LED
Input Voltage	120V-277V
Frequency	50/60 Hz
EPA	0.35 ft ²
Weight	13.6 lbs (luminaire only)


The Slope luminaire is aluminum extrusion with a natural aluminum powdercoat finish offered by Urbidermis with a clear or opal/diffused tempered glass.

Pole & Wall Mount Luminaire			
_____	Product	SPL	
_____	LED Configuration	18	36
_____	Drive Current	A (350 mA)	B (500 mA) C (700 mA)
_____	Color Temperature	1 (3000K)	2 (4000K)
_____	Distribution	TII (Type II)	TIII (Type III) TIV (Type IV)
_____	Lens	Null (Clear)	O (Opal / Diffused)
_____	Color	AS (Aluminum Silver)	DK (Dusk)


EXAMPLE: SPL – 18 – B – 1 – TII – AS

Mounting Accessories				
_____	Product	SPL		
_____	Bracket	01 (Single Column)	02 (Wall)	04 (Single Column Retrofit) 05 (Double Column Retrofit)
_____	Color	AS (Aluminum Silver)	DK (Dusk)	


EXAMPLE: SPL – 01 – DK



Single Column



Single Column, Back-to-Back



Wall

Slope Aluminum Pole Height	Pole #	Mounting	Diameter	Wall	Weight
3.4m (11.2 ft)	SPF11P	(1) Single Column Bracket	Straight 4.5"	0.125"	29 lbs
	SPF13P	(2) Single Column Brackets, Back-to-Back	Straight 4.5"	0.125"	29 lbs
4.2m (13.8 ft)	SPF21P	(1) Single Column Bracket	Straight 4.5"	0.125"	33 lbs
	SPF22P	(2) Single Column Brackets, Staggered Heights, 180° Orientation	Straight 4.5"	0.125"	33 lbs
	SPF23P	(2) Single Column Brackets, Back-to-Back	Straight 4.5"	0.125"	33 lbs
5.0m (16.4 ft)	SPF31P	(1) Single Column Bracket	Straight 4.5"	0.125"	38 lbs
	SPF32P	(2) Single Column Brackets, Staggered Heights, 180° Orientation	Straight 4.5"	0.125"	38 lbs
	SPF33P	(2) Single Column Brackets, Back-to-Back	Straight 4.5"	0.125"	38 lbs
5.8m (19.0 ft)	SPF41P	(1) Single Column Bracket	Straight 4.5"	0.188"	62 lbs
	SPF42P	(2) Single Column Brackets, Staggered Heights, 180° Orientation	Straight 4.5"	0.188"	62 lbs
	SPF43P	(2) Single Column Brackets, Back-to-Back	Straight 4.5"	0.188"	62 lbs
6.6m (21.7 ft)	SPF51P	(3) Single Column Brackets, Spiral Configuration, 120° Orientation	Stepped 6"/4.5"	0.188"	80 lbs

Pole Options							
_____	Twist Lock	Null (None)	T (Twist Lock Receptacle)				
_____	Color	BLK (Black)	DSK (Dusk)	MBK (Matte Black)	MER (Mercury) *	SIL (Silver)	SCL (Storm Cloud) TNM (Titanium)

* Mercury from Landscape Forms is our recommended color match for aluminum silver from Urbidermis.

EXAMPLE: SPFA2P – T – MER

Modifications

Don't see what you are looking for? Our goal is to partner with you as the designer to manufacture solutions needed for the space you are creating. We offer the option to modify our standard product to meet certain design specifications or needs. Common modifications can include GCFI outlets, custom RAL colors, banner arm(s) mounting, and custom pole heights. Contact your local Landscape Forms representative to learn more about these offerings.

Notes

Please send completed forms to your Landscape Forms representative or contact us at (800) 430-6209 with any questions.