




































Lighting Guide


































































Accent Lighting

| Product | Mounting Heights | Distribution Types | Delivered Lumens | Buy America Compliant | Other |
|--|---|---|------------------|-----------------------|---|
|  Arne | 13.8 ft (4.2 m), 16.4 ft (5 m), 19 ft (5.8 m), 25 ft (7.6 m), 30.2 ft (9.2 m) | Type II, Type III, Type IV, Type V, Type II+II, Wide Flood, Flood, Medium, Spot | 1900-9200lm | -- |    |
|  Arne S | 11.5 ft (3.5 m), 13.8 ft (4.2 m), 16.4 ft (5.0 m), 19 ft (5.8 m) | Type II, Type III, Type IV, Wide Flood, Flood, Medium, Spot, Oval, Light Blade | 800-2600lm | -- |    |
|  Gunnar | 12 ft (3.7 m), 14 ft (4.3 m), 16 ft (4.9 m), 20 ft (6.1 m) | Type II, Type III, Type IV, Type V, Type II+II, Wide Flood, Flood, Medium, Spot | 1100-4400lm | -- |    |
|  Moment | 12 ft (3.7m), 14 ft (4.3m), 16 ft (4.9m), 20 ft (6m), 25 ft (7.9m) | Spot, Medium, Flood, Wide Flood | 1350-9300lm | -- |    |
|  Profile | 10 ft (3.1 m), 12 ft (3.7 m), 14 ft (4.3 m), 16 ft (4.9 m) | Type II | 300-550lm | ✓ |   |
































Area Lighting (Streetscape & Pedestrian)
















| Product | Mounting Heights | Distribution Types | Delivered Lumens | Buy America Compliant | Other |
|---|---|---|------------------|-----------------------|---|
|  Alcott | 12 ft (3.7 m), 14 ft (4.3 m), 16 ft (4.9 m) | Type III, Type V | 2800-5700lm | ✓ |    |
|  Arne | 13.8 ft (4.2 m), 16.4 ft (5 m), 19 ft (5.8 m), 25 ft (7.6 m), 30.2 ft (9.2 m) | Type II, Type III, Type IV, Type V, Type II+II, Wide Flood, Flood, Medium, Spot | 1900-9200lm | -- |    |
|  Arne S | 11.5 ft (3.5 m), 13.8 ft (4.2 m), 16.4 ft (5.0 m), 19 ft (5.8 m) | Type II, Type III, Type IV, Wide Flood, Flood, Medium, Spot, Oval, Light Blade | 800-2600lm | -- |    |
|  Ashbery | 8 ft (2.4m), 10 ft (3.1m), 12 ft (3.7 m), 14 ft (4.3 m), 16 ft (4.9 m) | Type II, Type III, Type IV, Type V | 1000-8400lm | ✓ |    |





Lighting Guide

| Area Lighting (Streetscape & Pedestrian) (cont.) | | | | | |
|--|--|--|------------------|-----------------------|---|
| Product | Mounting Heights | Distribution Types | Delivered Lumens | Buy America Compliant | Other |
|  Candela | 19.7 ft (6 m), 26.3 ft (8 m), 32.8 ft (10 m) | Type II, Type III, Type IV | 5900-19600lm | -- |     |
|  FGP | 12 ft (3.7 m), 14 ft (4.3 m), 16 ft (4.9 m) | Type III, Type V | 2800-4000lm | ✓ |   |
|  Gunnar | 12 ft (3.7 m), 14 ft (4.3 m), 16 ft (4.9 m), 20 ft (6.1 m) | Type II, Type III, Type IV, Type V, Type II+II, Wide Flood, Flood, Medium, Spot | 1100-4400lm | -- |    |
|  Hi-Glo | 12 ft (3.7 m), 14 ft (4.3 m) | Type III | 3100lm | ✓ |    |
|  LEO | 12 ft (3.7 m), 16 ft (4.9 m), 20 ft (6.1 m), 25 ft (7.6 m) | Type II, Type III, Type IV | 2800-8100lm | ✓ |    |
|  Moment | 12 ft (3.7m), 14 ft (4.3m), 16 ft (4.9m), 20 ft (6m), 25 ft (7.9m) | Type I, Type II, Type III, Type IV, Type V | 2000-9700lm | -- |    |
|  Motive | 10 ft (3.1 m), 12 ft (3.7 m) | Type IV, Type V, Lambertian | 1400-4100lm | ✓ |    |
|  Northport | 12 ft (3.7 m), 14 ft (4.3 m), 16 ft (4.9 m) | Type II, Type III, Type IV, Type V | 2500-8300lm | ✓ |    |
|  Outline | 10 ft (3.1 m), 12 ft (3.7 m) | Type III, Type V | 925-2300lm | ✓ |     |
|  Profile | 10 ft (3.1 m), 12 ft (3.7 m), 14 ft (4.3 m), 16 ft (4.9 m) | Type II, Type III, Type IV | 1950-4550lm | ✓ |    |
|  Rama | 14.8 ft (4.5 m), 19.7 ft (6.0 m), 26.2 ft (8.0 m), 29.5 ft (9.0 m) | Type I, Type II, Type III, Type IV | 1300-17800lm | -- |     |
|  Slope | 11.2 ft (3.4 m), 13.8 ft (4.2 m), 16.4 ft (5.0 m), 19 ft (5.8 m), 21.7 ft (6.6 m) | Type II, Type III, Type IV | 2300-8100lm | -- |     |
|  Torres | 12 ft (3.7 m), 16 ft (4.9 m), 20 ft (6.1 m), 25 ft (7.6 m) | Type II, Type III, Type IV | 2500-7800lm | ✓ |    |
|  Tumbler | 11.2 ft (3.4 m), 13.8 ft (4.2 m), 16.4 ft (5.0 m), 19 ft (5.8 m), 21.7 ft (6.6 m) | Type II, Type III, Type IV, Type V, Wide Flood, Flood, Medium, Spot | 1900-4800lm | -- |    |
|  Typology | 12 ft (3.7 m), 14 ft (4.3 m), 16 ft (4.9 m), 20 ft (6.1 m), 25 ft (7.6 m) | Type V | 1450-7500lm | ✓ |    |










Lighting Guide






























| Catenary & Pendant Lighting | | | | |
|---|---|------------------|-----------------------|---|
| Product | Distribution Types | Delivered Lumens | Buy America Compliant | Other |
|  Arne | Type II, Type III, Type IV, Type V, Type II+II, Wide Flood, Flood, Medium, Spot | 1900-9200lm | -- |     |
|  Arne S | Type II, Type III, Type IV, Wide Flood, Flood, Medium, Spot, Oval, Light Blade | 800-2600lm | -- |     |
|  Gunnar | Type II, Type III, Type IV, Type V, Type II+II, Wide Flood, Flood, Medium, Spot | 1100-4400lm | -- |    |
|  Louis | Type II+II, Type V | 2000-9000lm | |    |
|  Moment | Type I, Type II, Type III, Type IV, Type V, Spot, Medium, Flood, Wide Flood | 1350-6800lm | -- |    |
|  Motive | Lambertian | 1500lm | ✓ |    |
|  Tumbler | Type V, Wide Flood, Type II+II | 1700-4400lm | -- |     |

| Column Lighting | | | | | |
|--|---|------------------------------------|------------------|-----------------------|---|
| Product | Mounting Heights | Distribution Types | Delivered Lumens | Buy America Compliant | Other |
|  Outline | 10 ft (3.1 m), 12 ft (3.7 m) | Type III, Type V | 925-2300lm | ✓ |     |
|  Profile | 10 ft (3.1 m), 12 ft (3.7 m), 14 ft (4.3 m), 16 ft (4.9 m) | -- | 150lm | ✓ |   |
|  SHUFFLE | 10 ft (3 m), 11.8 ft (3.6 m), 14.3 ft (4.4 m), 16.2 ft (4.9 m), 18.1 ft (5.5 m) | Type II, Type III, Type IV, Type V | 2100-6400lm | -- |    |
|  Typology | 10 ft (3.1 m), 13 ft (4.0 m), 16 ft (4.9 m) | Type I | 200-400lm | ✓ |   |

| Floor Lamp Lighting | | | | |
|--|--------------------|------------------|-----------------------|---|
| Product | Distribution Types | Delivered Lumens | Buy America Compliant | Other |
|  Motive | Lambertian | 300lm | ✓ |    |



Lighting Guide

| Outdoor Power | | | | |
|---|--------------------|------------------|-----------------------|---|
| Product | Distribution Types | Delivered Lumens | Buy America Compliant | Other |
|  Charging Station Accent Light | -- | -- | ✓ |   |
|  Charging Station Area Light | -- | 450lm | ✓ |   |
|  Power Pedestal | -- | Unlit | ✓ |   |





































| Path Lighting & Bollards | | | | |
|--|--------------------|------------------|-----------------------|---|
| Product | Distribution Types | Delivered Lumens | Buy America Compliant | Other |
|  Annapolis | -- | 50lm | ✓ | -- |
|  Annapolis | -- | Unlit | ✓ | -- |
|  Ashbery | Type IV, Type V | 400-900lm | ✓ |    |
|  FGP | Type III, Type V | 300-600lm | ✓ |   |
|  Guide | -- | 250lm | ✓ |   |
|  Guide | -- | Unlit | ✓ | -- |
|  Hawthorne | Type IV, Type V | 300-700lm | ✓ |    |
|  Lo-Glo | Type IV | 300lm | ✓ |    |
|  Motive | Type IV, Type V | 1000lm | ✓ |    |
|  MultipliCITY | Type IV, Type V | 500-1000lm | ✓ |    |

Lighting Guide

| Path Lighting & Bollards (cont.) | | | | | |
|---|--------------------|------------------|-----------------------|---|--|
| Product | Distribution Types | Delivered Lumens | Buy America Compliant | Other | |
|  Northport | Type IV, Type V | 600-1100m | ✓ |  | |
|  Northport | -- | Unlit | ✓ | -- | |
|  Outline | Type III, Type V | 600-1100lm | ✓ |  | |
|  Outline | -- | Unlit | ✓ | -- | |
|  Profile | Type IV, Type V | 450-950lm | ✓ |  | |
|  Profile | -- | 50lm | ✓ |  | |
|  Profile | -- | Unlit | ✓ | -- | |
|  Sentinel | -- | Unlit | ✓ | -- | |
|  Stop | -- | 50lm | ✓ |  | |
|  Stop | -- | Unlit | ✓ | -- | |
|  Torres | Type III | 200lm | ✓ |  | |

| Smart City | | | | | |
|---|--|------------------------------------|------------------|-----------------------|---|
| Product | Mounting Heights | Distribution Types | Delivered Lumens | Buy America Compliant | Other |
|  SHUFFLE | 10 ft (3 m), 11.8 ft (3.6 m), 14.3 ft (4.4 m), 16.2 ft (4.9 m), 18.1 ft (5.5 m) | Type II, Type III, Type IV, Type V | 2100-6400lm | -- |  |

Lighting Guide

| Wall Mount Lighting | | | | | |
|---|---|------------------|-----------------------|---|--|
| Product | Distribution Types | Delivered Lumens | Buy America Compliant | Other | |
|  Arne | Type II, Type III, Type IV, Type V, Type II+II, Wide Flood, Flood, Medium, Spot | 2000-9600lm | -- |    | |
|  Arne S | Type II, Type III, Type IV, Wide Flood, Flood, Medium, Spot, Oval, Light Blade | 800-2600lm | -- |    | |
|  Ashbery | Type III | 900lm | ✓ |    | |
|  Gunnar | Type II, Type III, Type IV, Type V, Type II+II, Wide Flood, Flood, Medium, Spot | 1100-4400lm | -- |    | |
|  Moment | Type I, Type II, Type III, Type IV, Type V, Spot, Medium, Flood, Wide Flood | 1350-9700lm | -- |    | |
|  Motive | Lambertian | 1700lm | ✓ |   | |
|  Slope | Type II, Type III, Type IV | 2300-8100lm | -- |     | |
|  Torres | Type III | 2100lm | ✓ |    | |
|  Tumbler | Type II, Type III, Type IV, Wide Flood, Flood, Medium, Spot | 1900-4800lm | -- |    | |